

INTERIOR MATT. EMULSION PAINT

WORLDTEX Interior



WORLDTEX Interior is an economical interior grade matt emulsion, suitable for use on most interior building surfaces.

Usage

WORLDTEX Interior can be used on new or old surfaces of concrete, brickwork, plasterwork, plywood. It is suitable for housing development, industrial and commercial complexes.

Application Procedure

Procedure	<ol style="list-style-type: none">1. Surface Preparation<ol style="list-style-type: none">1) All surfaces must be free of dust, sand, soil, and oil.2) When repairing, all previously painted residues must be removed.2. Environmental Conditions<ol style="list-style-type: none">1) Air temperature: 5 ~ 35 °C2) Relative humidity: up to 80%3) The surface temperature must be at least 5°C above the dew point to prevent moisture condensation3. Application Equipment Brush, roller, spray
Caution for usage	<ol style="list-style-type: none">1. Mixed paints should be used within pot life2. Do not mix with other paints3. Avoid applying paint on rainy days, high humidity(over 80%), low temperature (below 5°C), and high temperature (over 40°C surface temperature). (Coating film crack, adhesion failure, bubble generation may occur)4. When applying over a pre-coated surface, refer to the manufacturer's Application System for instruction.5. Please use this product within the validity period because it may be deteriorated since this product is a chemical product.
Caution for handling	<ol style="list-style-type: none">1. Do not use any other purpose2. Protect from freezing3. Keep out of reach of infants and children. Do not apply to infants, children's equipment or food storage containers.4. Avoid access to direct sunlight and fire when transporting, storing and handling, and store in a dry, cold place at room temperature(5~35°C)5. Please keep this product container sealed so that the injection port faces upward.6. Be careful that the paint does not come into contact with eyes and skin.7. If paint comes in contact with eyes and skin, wash thoroughly with running water and seek medical attention8. If inhaled or ingested, please seek medical advice immediately and follow the medical advice given in the container9. Avoid work in a confined space, and if you unintentionally paint, ventilate it thoroughly with exhaust system before working10. The best way to preserve paint is to store it in an airtight container to keep the water from evaporating and prevent microorganisms from getting in11. Dispose of the waste paint through the waste disposal company designated by the Ministry of Environment12. For other inquiries, please contact our Customer Service Center or refer to the Material Safety Data Sheet(GHS-MSDS), Technical Data.
Warning	Please consult our enclosed here with warning notice
Packing & Storage	Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

INTERIOR MATT. EMULSION PAINT

WORLDTEX Interior



Physical Data

Finish	Matt	Recommended Thickness	30~50 μ m
Product	INTERIOR MATT. EMULSION PAINT	Consumption	17.6m ² /L (DFT 30 μ m, Depends on the substrate's condition)
Specific Gravity	1.45	Packing Unit	18L containers
Coats	1~2	Shelf Life	24 months (in original unopened containers)
Volume Solid (%)	53 \pm 3		

The information given in this document is based on laboratory tests and on-site application results, but may vary depending on quality improvement and work conditions.

2020/07/01